



NBi Dispenser

FLEXIBLE ARCHITECTURE

USER-FRIENDLY INTERFACE

SMART POWER BALANCE

BUS PLUS READY

BACK-OFFICE INTEGRATION OCPP 1.6




THE COMBINATION OF MODULARITY AND HIGH PERFORMANCE

NBi Dispenser is an outdoor robust and modular charger, designed for durability, reliability and ease of maintenance. Thanks to its flexible architecture NBi Dispenser series allows the installation in any location. The charging solution consists of a power cabinet with low voltage input, which combines with industrial posts. With output power of up to 150 kW in DC (180 kW in US), NBi Dispenser allows the simultaneous charging of three vehicles thanks to the advanced functionality, Smart Power Balance. NBi Dispenser can be configured to charge either at 400 or 800 Vdc depending on the characteristics of the electric vehicle battery. Its smart design offers a simple, fast and safe charging experience, which makes it being the best solution for sites with space reduced that require maximum return on investment.

FLEXIBLE ARCHITECTURE

NBi Dispenser is the charging solution for locations where space is at a premium.

The NBi Dispenser series is a DC charging solution with low voltage input consisting of a power cabinet which supplies energy to industrial charging posts. The available power cabinet configurations are from 50 kW to 150 kW (from 60 kW up to 180 kW in US) and are combined with DC post of 50, 100 and 150 kW (60, 120 and 180 kW in US).



USER-FRIENDLY INTERFACE

Intuitive experience

Power Electronics posts integrate a status indicator so that the drivers can easily identify its availability. It provides drivers a fast, safe and simple interaction.

Payment and authentication system

Every charging post is compatible with any payment and authentication system, offering the most useful solutions in the market for an easy interaction with the customer.



RFID

Drivers can launch a charging session by tapping their RFID card.



Credit / Debit card

Compatibility with contact-less (NFC) solutions, letting drivers initiate the charging process by simply tapping their credit/debit card.



Smartphone

Compatible with the most extended apps in the market. These apps for EV drivers are able to start a charging session, reserve a post at any time, or simply manage their historical charging sessions.

SMART POWER BALANCE

Power Electronics has developed the most advanced functionality for power balancing in vehicle fleet management. Designed to minimize the initial investment and the operation costs.

Smart Power Balance functionality is able to balance the power based on the number of charging posts in use. Therefore, the total power required to supply the total energy gets substantially reduced, representing a cost reduction in the electrical facility infrastructure and a cost saving due to a minor power contracted. Besides, the hardware and the back-office communication is optimized.

CONFIGURATION EXAMPLE

NBD150S Industrial

Three charging posts NBD1100 of 100 kW

Vehicle 3
100 kW
Charging



Vehicle 2
50 kW
Available

Vehicle 1
0 kW
Completed charging



BUS PLUS READY

NBi Dispenser can connect to a DC power supply to provide electric vehicle charging power. The power source could be the photovoltaic energy, a battery system or the utility grid.



SMART AND CUSTOMIZABLE DESIGN

EXACTLY THE WAY YOU WANT

Customizable external enclosures

Power Electronics offers customizable external enclosures for the central power station and the posts. The color can be modified or logos and advertising can be added.

Vehicle detection

Optionally, it is possible to include the vehicle detection function, which allows starting the charging process when the car is close to the charging post.



EXAMPLES OF POST CUSTOMIZATIONS



NBI DISPENSER

IEC

REFERENCE	NBD050 NBD050S	NBD100 NBD100S	NBD150 NBD150S	
DC OUTPUT	Power cabinet maximum output power [kW]	50	100	150
	Post maximum power [kW]	50	50 / 100	50 / 100 / 150
	Voltage range [V]	50 - 500 / 150 - 1000		
	Available connectors	CCS-2 ^[1] , CHAdeMO, GB/T		
AC OUTPUT	Power [kW]	53	105	158
	Voltage [V]	400 ± 10 %		
	Power factor	> 0.99		
	Frequency [Hz]	50 / 60		
	Efficiency	95%		
GENERAL	Interface	Post status LED indicator		
		Button to stop charging		
		Emergency stop (optional)		
	Protections	Isolation monitor		
		Over-voltages / under-voltages		
		Over-currents / short-circuits		
		RCD		
		Over-temperatures		
	Others	Smart Power Balance (optional)		
		Vehicle detection (optional)		
	Cable length [m] ^[2]	4		
	Degree of protection	IP54 / IK10 ^[3]		
	Operating temperature	From -20°C to 60°C (optionally, from -35°C to 60°C)		
	Relative humidity	4% - 95%		
	Maximum altitude (above sea level)	2000 m		
Customization	Enclosure			
Communications	OCPP 1.6, Ethernet, 3G/4G connectivity (optional), Wifi (optional)			
Post dimensions (W x D x H) [mm]	600 x 300 x 800			

STANDARD CONFIGURATION

REFERENCE	SMART POWER BALANCE	POSTS		
		NBDI050	NBDI100	NBDI150
NBD050	-	1	-	-
NBD100	-	2	1	-
NBD100S	√	-	2	-
NBD150	-	3	-	1
NBD150S	√	-	3	3

[1] CCS-1 on demand

[2] Optional cable length 7 m.

[3] IK08 for ventilation grilles.

NBI DISPENSER

US

REFERENCE	NBD060 NBD060S	NBD120 NBD120S	NBD180 NBD180S		
DC OUTPUT	Power cabinet maximum output power [kW]	60	120	180	
	Post maximum power [kW]	60	60 / 120	60 / 120 / 180	
	Voltage range [V]	50 - 500 / 150 - 1000			
	Available connectors	CCS-1, CHAdeMO, GB/T			
AC OUTPUT	Power [kW]	63	126	189	
	Voltage [V]	480 ± 10 %			
	Power factor	> 0.99			
	Frequency [Hz]	60			
	Efficiency	95%			
GENERAL	Interface	Post status LED indicator			
		Button to stop charging			
		Emergency stop (optional)			
	Protections		Isolation monitor		
			Over-voltages / under-voltages		
			Over-currents / short-circuits		
			RCD		
			Over-temperatures		
	Others		Smart Power Balance (optional)		
			Vehicle detection (optional)		
	Cable length [ft] ^[1]	13.12			
	Degree of protection	NEMA 3R			
	Operating temperature	From -20°C to 60°C (optionally, from -35°C to 60°C)			
	Relative humidity	4% - 95%			
Maximum altitude (above sea level)	2000 m				
Customization	Enclosure				
Communications	OCPP 1.6, Ethernet, 3G/4G connectivity (optional), Wifi (optional)				
Post dimensions (W x D x H) [ft]	2.0 x 1.0 x 2.6				

STANDARD CONFIGURATION

REFERENCE	SMART POWER BALANCE	POSTS		
		NBDI060	NBDI120	NBDI180
NBD060	-	1	-	-
NBDD120	-	2	1	-
NBD120S	√	-	2	-
NBD180	-	3	-	1
NBD180S	√	-	3	3

[1] Optional cable length 22.97 ft.